

Wireless belt-pack microphone with true diversity UHF receiver.

Several frequency banks available, 863-865 MHz, 823-832 MHz, 631-645 MHz, 570-582 MHz and 512-525 MHz. Double circuit receiver for optimum reception.

Great quality sound.



MSH-883-512

FREQUENCIES	512-525 MHz 32 channels
RESPONSE	40-18,000 Hz
OUTPUTS	1 balanced, XLR 1 unbalanced, 6.3 mm jack
S/N RATIO	> 105 dB
MICROPHONES	1 tie-clip microphone with unidirectional electret condenser capsule and wireless belt-pack transmitter with mic./line input sensitivity selector
POWER	10 mW maximum
POWER SUPPLY	Receiver: 12.8 V DC, 250 mA, with adapter included Transmitter microphone: 2 x LR6-AA batteries. Accepts rechargeable batteries
DIMENSIONS	Receiver: 210 x 45 x 156 mm depth
WEIGHT	1.7 kg
ACCESSORIES	Mounts for assembly of 2 receivers in 1 U 19" rack 6.3 mm mono jack cable Rechargeable batteries
OPTIONAL	MSC-2, MSC-12 and MSC-24: wireless microphone recharge docking stations ANG-5L: mount for assembling in 19" rack